

Technical Data Sheet



THEVA Pro-Line TPL1100

High current second generation HTS wire with surround silver stabilization.

Technical Specifications

Tape architecture

Substrate	Hastelloy™ C-276, non-magnetic
Buffer layer	MgO
HTS layer	GdBa ₂ Cu ₃ O ₇
Metallization	~ 1 μm Silver surround
Stabilizer	none

Mechanical properties

Thickness	0.10 – 0.12 mm
Width	11.8 - 12.2 mm
Minimum double bend diameter (RT)	60 mm
Recommended maximum handling force	100 N (10 kg) ¹
Maximum rated stress (RT)	600 MPa ²
Maximum rated tensile strain (77 K)	0.3% ²

Electrical properties

Minimum critical current I _c (77 K, self-field) ³	360 A, other current ratings upon request
---	---

Marks on tape back (substrate) side

Every meter	Meter period and type
Every 20 cm	⚠, symbol indicating the c-axis tilt direction ⁴
Ink	Black ink ⁵

Handling

	handle with care
	handle with gloves
	store in dry ambient (<50% rel. humidity) below 50°C

¹ Recommended maximum pulling strength for handling with rollers (100mm diam.)

² 95% I_c-retention

³ Measured by high resolution continuous TapeStar™ XL scanning (Hall sensors) calibrated to 1 μV/cm

⁴ Detailed information on angle definition and magnetic field properties upon request

⁵ Ink removable with isopropanol or organic solvents